

PVC Tubing

Features and Benefits

A thin wall section makes P sleeving ideal for minimising the overall diameter of loom assemblies.

Application

These high-grade PVC sleeves (P) have a thin wall that makes them ideal for insulating wire in areas where space is at a premium. They can be supplied as continuous tubing or cut lengths. The tubing is available in international resistor colour code, pink and transparent.



Helvin P tubing.

Technical Table

Code	Supplied Ø D	Wall (WT) nom.
PVC1	1	1.0
PVC2	2	1.0
PVC3	3	1.0
PVC4	4	1.0
PVC5	5	1.0
PVC6	6	1.0
PVC8	8	1.0
PVC10	10	1.0
PVC12	12	1.0
PVC13	13	1.0
PVC14	14	1.0
PVC16	16	1.0
PVC18	18	1.0
PVC19	19	1.0
PVC20	20	1.0
PVC22	22	1.0
PVC23	23	1.0
PVC24	24	1.0
PVC25	25	1.0
PVC30	30	1.0
PVC35	35	1.0

All dimensions in mm. Subject to technical changes.

Std Pack Sizes: 1-20 mm ID = 100 m rolls, 22-35 mm ID = 50 m rolls

Min Order Qty: As per standard Pack of 500 mm, except black sizes 2, 4, 6, 8 and 10 mm

Standard Colour - Black. Other colours on request.



Material Data

RoHS	Material	PVC (Polyvinylchloride)
	Operating Temperature	-65°C to +105°C, Intermittent +135°C
	Flammability	UL94 V0 at 1mm thickness, Self extinguishing
	Specification	UL224, BS 3858 Type 3, IEC 684-3-101 / 104, DEF STAN 59-15



Please Note for Product Specific Approvals please refer to Appendix.