


## Insulated Female Disconnects




Technical Table

Code	Wire Range (mm <sup>2</sup> )	Colour	Dimensions		
			W	L	F
1DF2	0,25 - 1,65	Red	3,2	18,6	6,5
1DF4			5,0	19,0	6,4
1DF			6,6	20,5	7,3
2DF4	1,04 - 2,63	Blue	5,0	19,0	6,4
2DF			6,6	20,5	7,3
2DF9			10,0	25,5	12,0
3DF	2,63 - 6,64	Yellow	6,6	23,5	7,3
3DF9			10,0	28,5	12,0

For Inner Copper Tube (TwinGrip) use Prefix "T"

## Fully Insulated Female Disconnects




Technical Table

Code	Wire Range (mm <sup>2</sup> )	Colour	Dimensions		
			W	L	F
F1DF2	0,25 - 1,65	Red	3,8	19,0	6,4
F1DF4			5,0	19,3	6,4
F1DF			6,6	22,0	7,3
F2DF4	1,04 - 2,63	Blue	5,0	19,3	6,4
F2DF			6,6	22,0	7,3
F3DF			6,6	24,0	7,3
F3DF9	2,63 - 6,64	Yellow	10,0	28,5	12,0

For Inner Copper Tube (TwinGrip) use Prefix "T"

## Insulated Piggy Back Disconnects




Technical Table

Code	Wire Range (mm <sup>2</sup> )	Colour	Dimensions		
			W	L	F
1PB	0,25 - 1,65	Red	6,6	22,0	8,0
2PB	1,04 - 2,63	Blue	6,6	22,0	8,0

For Inner Copper Tube (TwinGrip) use Prefix "T"

## Insulated Male Bullet Disconnects




Technical Table

Code	Wire Range (mm <sup>2</sup> )	Colour	Dimensions		
			W	L	F
1ULM4	0,25 - 1,65	Red	4,0	21,5	8,5
2ULM4	1,04 - 2,63	Blue	4,0	21,5	8,5
3ULM4	2,63 - 6,64	Yellow	4,0	24,0	8,5
3ULM5			5,0	24,0	8,5

For Inner Copper Tube (TwinGrip) use Prefix "T"

## Insulated Female Bullet Disconnects



Technical Table

Code	Wire Range (mm <sup>2</sup> )	Colour	Dimensions		
			W	L	F
1ULF4	0,25 - 1,65	Red	3,9	21,5	7,3
2ULF4	1,04 - 2,63	Blue	3,9	25,5	7,3
2ULF5			5,9	25,5	7,0
3ULF5	2,63 - 6,64	Yellow	4,9	24,5	7,0

For Inner Copper Tube (TwinGrip) use Prefix "T"

● 0.5 - 1,5mm<sup>2</sup> - 19Amp 600V    ● 1.5 - 2,5mm<sup>2</sup> - 27Amp 600V    ● 4 - 6mm<sup>2</sup> - 48Amp 600V