

TSP1A Surge Plug Top

- 3 protective elements
- Economical secondary protection
- 2 Year Warranty

Rated Voltage	275V/50Hz
Max Continuous Current	2,5kA
Max Discharge Current	8kA
Response Time	25ns
Residual Voltage	Approx.900V
Temperature Range	-10°C ~70°C
Standards Compliance	IEC 61643-1, IEC 99,4, ANSI C 62,41



TSP1AI Surge Plug Top

- 3 protective elements with indicator
- Economical secondary protection
- 2 Year Warranty

Rated Voltage	275V/50Hz
Max Continuous Current	2,5kA
Max Discharge Current	8kA
Response Time	25ns
Residual Voltage	Approx.900V
Temperature Range	-10°C ~70°C
Standards Compliance	IEC 61643-1, IEC 99,4, ANSI C 62,41



TSP1AF Surge Plug Top

- 3 protective elements (Flat Earth)
- Economical secondary protection
- 2 Year Warranty

Rated Voltage	275V/50Hz
Max Continuous Current	2,5kA
Max Discharge Current	8kA
Response Time	25ns
Residual Voltage	Approx.900V
Temperature Range	-10°C ~70°C
Standards Compliance	IEC 61643-1, IEC 99,4, ANSI C 62,41

